

# LAMM

## C900

Baldanzi & Novelli

### Technical features

Armchair for conference halls and auditoriums.

#### Seat and backrest

Seat and backrest with tubular steel internal structure and padding in flame-retardant polyurethane foam. Backrest with strengthened elastic belts.

Synchronized tip-up system for seat and back through a patented mechanism.

The rear backrest can be fully padded or supplied with a low painted wood carter panel in eucalyptus, oak or grey oak finishes.

Covered with fabric, eco-leather or leather.

#### Sides

Sides with steel internal structure and MDF panels covering the structure.

10 cm deep padded sides, or upholstered or covered added wood armrest in oak, grey oak and eucalyptus finishes.

Covered with fabric, eco-leather or leather.

Sides with added armrest also available with stratified HPL tip-up writing tablet with black finishes and anti-panic movement, that folds away into the side.

Floor fixing feet in steel profiles, painted with scratchproof epoxy powder in semi-matt black RAL 9005, semi-matt silver, embossed bronze and embossed graphite finishes.

Installation on horizontal and inclined flooring or on steps, in straight or curved rows (minimum radius 8 m.). Centre to centre distance cm. 56, 58 and 60.

#### Accessories

Black stratified HPL tip-up writing table with anti-panic movement.

Seat numbering and row identification element.

Painted wood low backrest panel with oak, grey oak or eucalyptus finishes (positioned in the lower part).

Painted wood under seat panel with oak, grey oak or eucalyptus finishes.

Optional system allowing armchairs to be moved away on wheels in 2 or 3 seat units when unused (for floor-fixing armchair in straight rows)

Electric power supply provision (socket on demand).